

Specifications	AMCB-20	AMCB-30	AMCB-45	AMCB-60
Capacity	25M <sup>3</sup> /HR	30M <sup>3</sup> /HR	45M <sup>3</sup> /HR	60M <sup>3</sup> /HR
Mixer	Twin shaft	Twin shaft	Twin shaft	Twin shaft
Inline Bin	4	4	4	4
Capacity of each Bin	2.5	4.5	7.5	10
Output Capacity	350 liters.	500 liters.	750 liters.	1000 liters.
Cycle time	60 sec.	60 sec.	60 sec.	60 sec.
Weighing System	Electronic digital	Electronic digital	Electronic digital	Electronic digital
Cement / Fly Ash Weighing capacity	200 Kg.	250 Kg.	300 Kg.	450 Kg.
Water Weighing Capacity	150 liter	200 liter	200 liter	300 liter
Additive Capacity	10 Kg.	10 Kg.	10 Kg.	15 Kg.
Load out belt conveyor width	650 mm	800 mm	800 mm	1000 mm
Air Compressor				
Connected power	3HP	3HP	5HP	7.5HP
Cylinder	2	2	2	2
Max Pressure	12.3 KG	12.3 KG	12.3 KG	12.3 KG
Piston Displacement	10.80 CFM	10.80 CFM	17.32 CFM	20.00 CFM
Cement Screw Conveyor				
Diameter	219	219	219	219
Connected Power	12.5 HP	12.5 HP	12.5 HP	12.5 HP
Control Panel	PLC based auto manual option	PLC based auto manual option	PLC based auto manual option	PLC based auto manual option
Discharge Height	4 mtr.	4 mtr.	4 mtr.	4 mtr.
Total Connected load	55 HP.	67 HP	78.5 HP	110 HP