

Specifications	AMCB-10	AMCB-15	AMCB-20
Capacity	10M ³ /HR	15M ³ /HR	20M ³ /HR
Mixer	Reversible drum	Reversible drum	Reversible drum
Inline bin	2 x 4	2 x 4	2 x 4
Capacity of each Bin	2.5	3.5	4.5
Output Capacity	400 ltr.	600 ltr.	800 ltr.
Cycle time	80 sec.	80 sec.	80 sec.
Weighing System	Electronic digital	Electronic digital	Electronic digital
Cement / Fly Ash Weighing capacity	150 Kg.	200 Kg.	200 Kg.
Water Weighing Capacity	200 liter	200 liter	250 liter
Additive Capacity	10 Kg.	10 Kg.	10 Kg.
Load out belt conveyor width	600 mm	650 mm	650 mm
Air Compressor			
Connected power	3HP	3HP	3HP
Cylinder	2	2	2
Max Pressure	12.3 KG	12.3 KG	12.3 KG
Piston Displacement	10.80 CFM	10.80 CFM	10.80 CFM
Cement Screw Conveyor			
Diameter	219 mm	219 mm	219 mm
Connected Power	6 HP	6 HP	6 HP
Control Panel	PLC based auto manual option	PLC based auto manual option	PLC based auto manual option
Discharge Height	1.5 mtr.	1.5 mtr.	1.8 mtr.
Total Connected load	35 HP.	40 HP	45 HP